

### **AUTOMATIC FEEDER TT133/4**



**€702,48 (excl. VAT)**

This automatic feeder is ideal for safely guiding workpieces past your spindle moulder. This feeder operates at four speeds. This allows you to work at your own pace, adapted to the hardness of the wood. The design with spring suspension generates constant and even pressure, allowing you to work precisely. With the help of a roller spring mechanism, the feeder easily accommodates small variations in thickness (up to 18 cm). Quickly and easily adjustable in height and speed. Equipped with easily replaceable wheels in PU. Additional wheels are available separately.

**SKU: 0FEM1334S**

## GALERIJAFBEELDINGEN



This automatic feeder is ideal for safely guiding workpieces past your spindle moulder. This feeder operates at four speeds. This allows you to work at your own pace, adapted to the hardness of the wood. The design with spring suspension generates constant and even pressure, allowing you to work precisely. With the help of a roller spring mechanism, the feeder easily accommodates small variations in thickness (up to 18 cm). Quickly and easily adjustable in height and speed. Equipped with easily replaceable wheels in PU. Additional wheels are available separately.

## PRODUCT INFORMATION

- Feeder
- For woodworking machines

## DESCRIPTION

This automatic feeder is ideal for safely guiding workpieces past your spindle moulder. This feeder operates at four speeds. This allows you to work at your own pace, adapted to the hardness of the wood. The design with spring suspension generates constant and even pressure, allowing you to work precisely. With the help of a roller spring mechanism, the feeder easily accommodates small variations in thickness (up to 18 cm). Quickly and easily adjustable in height and speed. Equipped with easily replaceable wheels in PU. Additional wheels are available separately.

No video available for this product!

### DOWNLOADS

No download available.

### ADDITIONAL INFORMATION

<b>Weight</b>	33 kg
<b>Voltage</b>	230 V
<b>No-load speed</b>	6m/min, 8m/min, 10m/min, 13m/min
<b>Ø wheel</b>	80mm
<b>Max. height work piece</b>	130mm