



BANDSAW TT500X - 230V



€1 .859,50 (excl. VAT)

Band saw machine equipped with a 230V induction motor and two speeds. Compared to classic machines with carbon brush motors, you have two advantages with this band saw. The induction motor is both quieter and more powerful. The wheel system guides the saw blade both above and below the worktable for optimal guidance. The work table of this band saw is completely in cast iron and can be tilted up to 45° or -10°. As standard, this machine is equipped with an accurate length guide and a mitre guide.

Equipped with an exhaust to connect dust extraction. A mobile base is available as an option.

Different widths of blade in hardened steel 'Flexback' available between 13mm and 32mm width, a bimetal blade (14 TPI) of 27mm width or a widia-set blade (3 TPI) of 27mm width.

SKU: 0BS500X

GALERIJAFBEELDINGEN



Powerful band saw equipped with a 230V induction motor (3HP) and two speeds. Suitable for solid work as well as more sophisticated circular sawing. Compared to classic machines with carbon brush motors, you have two advantages with this band saw. The induction motor is both quieter and more powerful. The wheel system guides the saw blade both above and below the worktable for optimal guidance. These wheels are fitted with a rubber coating to optimise the life of your blade. Finally, this machine has thick brushes to extend the life of the rubber. This band saw has a maximum cutting height of 280mm and a maximum width of 465mm. The height is easily adjustable thanks to the rotary knob and gear rack. The wheel housings are fitted with safety doors.

The work table of this band saw is completely in cast iron and can be tilted up to 45° or -10°. As standard, this machine is equipped with an accurate length guide and a mitre guide. It can be moved very easily over the work table in the slots provided for this purpose. The whole is very stable, partly thanks to the torsion free construction. The machine is equipped with an exhaust to connect dust extraction. A stable, maintenance-free construction with quiet, stable and, above all, precise running of the blade. With two built-in windows to control the running of the blade.

PRODUCT INFORMATION

- Torsion free construction
- Two speeds (420m/min - 840m/min)
 - Cast iron worktable (tiltable)
 - Depth control with rotary knob
 - Max. height: 280mm
 - Max. width: 465mm
 - Miter guide
 - Induction motor 3HP
 - Wheels with rubber and brush
 - Double ball bearing

DESCRIPTION

Powerful band saw equipped with a 230V induction motor (3HP) and two speeds. Suitable for solid work as well as more sophisticated circular sawing. Compared to classic machines with carbon brush motors, you have two advantages with this band saw. The induction motor is both quieter and more powerful. The wheel system guides the saw blade both above and below the worktable for optimal guidance. These wheels are fitted with a rubber coating to optimise the life of your blade. Finally, this machine has thick brushes to extend the life of the rubber. This band saw has a maximum cutting height of 280mm and a maximum width of 465mm. The height is easily adjustable thanks to the rotary knob and gear rack. The wheel housings are fitted with safety doors. The work table of this band saw is completely in cast iron and can be tilted up to 45° or -10°. As standard, this machine is equipped with an accurate length guide and a mitre guide. It can be moved very easily over the work table in the slots provided for this purpose. The whole is very stable, partly thanks to the torsion free construction. The machine is equipped with an exhaust to connect dust extraction. A stable, maintenance-free construction with quiet, stable and, above all, precise running of the blade. With two built-in windows to control the running of the blade.

No video available for this product!

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	162 kg
Dimensions	207 × 54,5 × 83 cm
Motor	3 HP
Voltage	230 V
Blade speed	420m/min, 840m/min
Work table	630x485mm
Table tilt	-10° - 45°
Max. cutting height	280mm
Max. width of cut	465mm
Length of blade	3607mm
Width of blade	13mm, 16mm, 20mm, 25mm, 27mm, 32mm