

## BERGER BAU - CONSTRUCTION TABLE SAW 450KBS WITH CUTTING HEIGHT 130MM, 7.5HP 400V



**€2 .768,60 (excl. VAT)**

The Berger Bau 450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and a cutting depth of approx. 130mm that can withstand the toughest construction conditions. The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw. This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload.

**SKU: BB-450KBS-A**

## GALERIJAFBEELDINGEN



The Berger Bau 450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and a cutting depth of approx. 130mm that can withstand the toughest construction conditions. The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw. This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload.

## PRODUCT INFORMATION

- Robust safety guard with connection for dust collector
- Fully enclosed lower frame with connection for dust collector
  - Aluminum insert plate
- Fixed Point Miter Gauge with Quick Clamp

- Rip fence with precision size indication and quick clamp
- High-quality German-made low-noise carbide saw blade (nail-proof)
  - Strong, magnetically braked motor Moll Austria 7.5 HP
  - Perfectly balanced hang up by means of 2 lifting eyes
    - Strong hot-dip galvanized frame
    - Phase changeover switch
    - Foldable table extension
    - Cutting depth Approx.130mm

## DESCRIPTION

The Berger Bau 450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and a cutting depth of approx. 130mm that can withstand the toughest construction conditions. The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw. This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload.

No video available for this product!

## DOWNLOADS

No download available.

## ADDITIONAL INFORMATION

<b>Weight</b>	125 kg
<b>Motor</b>	7.5 HP
<b>Voltage</b>	3 x 400V
<b>Working height</b>	850mm

<b>Cutting depth 90 °</b>	130 mm
<b>Worktable</b>	1046 x 750 mm
<b>Bore hole</b>	30 mm
<b>Diameter sawblade</b>	450mm
<b>Saw blade speed</b>	2850
<b>Dust collection port</b>	50 mm, 90 mm