

BERGER BAU - CONSTRUCTION TABLE SAW H450KBS WITH ADJUSTABLE CUTTING HEIGHT 140MM, 7.5HP 400V



€3 .388,43 (excl. VAT)

The Berger Bau H450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and an adjustable cutting depth of approx. 0-140mm that can withstand the toughest construction conditions.

The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw. This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload.

SKU: BB-H450KBS-A

GALERIJAFBEELDINGEN



The Berger Bau H450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and an adjustable cutting depth of approx. 0-140mm that can withstand the toughest construction conditions. The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw.

This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload.

Adjustable cutting height at H-450KBS

Cutting depth adjustable from 0-140 mm by means of robust handwheel and a scissor lift system and therefore no load on a single axle. This unique operation is also fully integrated; this prevents dirt or stiffness on the height control and ensures permanent smooth operation. The extremely stable motor suspension guarantees an exact cut at all times.

PRODUCT INFORMATION

- Robust safety guard with connection for dust collector
- Fully enclosed lower frame with connection for dust collector
 - Aluminum insert plate
- Fixed Point Miter Gauge with Quick Clamp
- Rip fence with precision size indication and quick clamp
- High-quality German-made low-noise carbide saw blade (nail-proof)
 - Strong, magnetically braked motor Moll Austria 7.5 HP
 - Perfectly balanced hang up by means of 2 lifting eyes
 - Strong hot-dip galvanized frame
 - Phase changeover switch
 - Foldable table extension
- Cutting depth adjustable 0 – 140 mm
 - Unique scissor lift system
 - Built-in heavy hand wheel

DESCRIPTION

The Berger Bau H450KBS is a professional 400V construction saw with a heavy induction motor 7.5HP and an adjustable cutting depth of approx. 0-140mm that can withstand the toughest construction conditions. The frame is strongly hot-dip galvanized and provided with a perfectly balanced hang up by means of only 2 lifting eyes. There is no need for a 4 piece hanger. The completely closed bottom frame is equipped with a large outlet for dust extraction. The insert plate along the saw blade is made of aluminum ground material (not PVC). The robust rip fence has a quick clamping device and therefore does not have to be blocked by means of a screw.

This does not damage the material. The miter gauge also features a quick clamping device and fixed adjustment points with a clear view. The machine is equipped with a phase changeover switch according to the new EUR standards. The safety switch prevents the machine from starting again after a power failure and protects the motor against overload. **Adjustable cutting height at H-450KBS** Cutting depth adjustable from 0-140 mm by means of robust handwheel and a scissor lift system and therefore no load on a single axle. This unique operation is also fully integrated; this prevents dirt or stiffness on the height control and ensures permanent smooth operation. The extremely stable motor suspension guarantees an exact cut at all times.

No video available for this product!

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	160 kg
Motor	7.5 HP
Voltage	3 x 400V
Working height	850mm
Cutting depth 90 °	140 mm
Worktable	1046 x 750 mm
Bore hole	30 mm
Diameter sawblade	450mm
Saw blade speed	2850
Dust collection port	50 mm, 90 mm