

## ELECTRONIC SURFACE ROUTERE FR278R



**€388,28 (excl. VAT)**

This router is identical to the FR277R but is equipped with an electronic speed control. Thanks to its light weight, this router is very manageable and suitable for most milling and copying work. The FR278R delivers high precision and stability while working. Ideal for deburring edges, copying, milling frames, etc. The milling depth is adjustable between 0-50mm and is easily adjusted using three fixed positions. The lateral conductor, in turn, is equipped with a micrometric control to work precisely at all times. Easy to set using a rotary knob. Equipped with a connection for dust extraction.

**SKU: VIR-FR278R**

## GALERIJAFBEELDINGEN



This router is identical to the FR277R but is equipped with an electronic speed control. Lightweight router from Virutex for milling wood or plastics. Thanks to its light weight, this router is very manageable and suitable for most milling and copying work. The FR278R delivers high precision and stability while working. Ideal for deburring edges, copying, milling frames, etc. The milling depth is adjustable between 0-50mm and is easily adjusted using three fixed positions. The lateral conductor, in turn, is equipped with a micrometric control to work precisely at all times. Easy to set using a rotary knob. Equipped with a connection for dust extraction.

## PRODUCT INFORMATION

- Router milling machine
  - Depth: 0-50mm
  - Lightweight
- For most common routing and copying work
  - Precision and stability
  - Electronic speed control

## DESCRIPTION

This router is identical to the FR277R but is equipped with an electronic speed control. Lightweight router from Virutex for milling wood or plastics. Thanks to its light weight, this router is very manageable and suitable for most milling and copying work. The FR278R delivers high precision and stability while working. Ideal for deburring edges, copying, milling frames, etc. The milling depth is adjustable between 0-50mm and is easily adjusted using three fixed positions. The lateral conductor, in turn, is equipped with a micrometric control to work precisely at all times. Easy to set using a rotary knob. Equipped with a connection for dust extraction.

No video available for this product!

## DOWNLOADS

No download available.

## ADDITIONAL INFORMATION

<b>Weight</b>	3,2 kg
<b>Input Power</b>	1300W
<b>No-load speed</b>	6000-27000rpm
<b>Routing depth</b>	0-50mm
<b>Collet</b>	8mm