

GRÖBE TT500DD-ES 230V





€822,31 (excl. VAT)

Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø500mm and an induction motor of 3.5 HP. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 180mm. Ergonomic and easy to operate, with automatic return unit.

Fully assembled on delivery and ready to use.

SKU: 0GL500DD-ES

GALERIJAFBEELDINGEN



Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. Includes zero voltage protection on the switch for improved safety in the event of voltage loss. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø500mm. The direct-drive induction motor delivers 3.5 HP. Use at least power cable with thickness 2.5m² to avoid damaging the motor. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 180mm.

The tilting saw is equipped with an automatic return unit using a spring. The saw blade is effortless to operate and cuts quickly through the wood. Saw large quantities of wood in one go without any problems and ergonomically. Using the extendable support and size indication, you can cut even longer pieces to the same size. Equipped with a sturdy base with two wheels and a pull rod which makes it easy to move the machine. Easy to move, both indoors and outdoors and on uneven surfaces. Fully assembled on delivery and ready to use.

PRODUCT INFORMATION

- Tilting log saw
- Compact design & mobile
- Carbide (widia) saw blade 500mm
 - Support for longer pieces
- Powerful induction motor with direct drive
 - Tip: use at least 2.5m² cable
- Long-term sawing without problems
 - Return unit with spring
- Maximum capacity round timber 180mm

DESCRIPTION

Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. Includes zero voltage protection on the switch for improved safety in the event of voltage loss. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø500mm. The direct-drive induction motor delivers 3.5 HP. Use at least power cable with thickness 2.5m² to avoid damaging the motor. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 180mm. The tilting saw is equipped with an automatic return unit using a spring. The saw blade is effortless to operate and cuts quickly through the wood. Saw large quantities of wood in one go without any problems and ergonomically. Using the extendable support and size indication, you can cut even longer pieces to the same size. Equipped with a sturdy base with two wheels and a pull rod which makes it easy to move the machine. Easy to move, both indoors and outdoors and on uneven surfaces. Fully assembled on delivery and ready to use.

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	130 kg
Dimensions	105 × 85 × 110 cm
Voltage	230 V
Motor	3.5 HP
Diameter sawblade	500mm
Max. cutting diameter	180mm