

## GRÖBE TT700BD-PTO-ES CARDAN DRIVE



**€1 .735,37 (excl. VAT)**

Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø700mm. This model is equipped with a three-point hitch and connection for PTO shaft. The machine can thus be powered by a tractor. Just like the other TT700 models, this sawing machine is equipped with belt drive. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 240mm.

Fully assembled on delivery and ready to use.

**SKU:** 0GL700PTO-ES

## GALERIJAFBEELDINGEN



Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. Includes zero voltage protection on the switch for improved safety in the event of voltage loss. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø700mm. This model is equipped with a three-point hitch and connection for PTO shaft. The machine can thus be powered by a tractor. Transmission to the saw blade with belt drive. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 240mm.

The tilting saw is equipped with an automatic return unit using a spring. The saw blade is effortless to operate and cuts quickly through the wood. Saw large quantities of wood in one go without any problems and ergonomically. Using the extendable support and size indication, you can cut even longer pieces to the same size. Equipped with a sturdy base with two wheels and a pull rod which makes it easy to move the machine. Easy to move, both indoors and outdoors and on uneven surfaces. Couple this tilting log saw to your tractor to be able to use it directly anywhere. Fully assembled on delivery and ready to use.

### PRODUCT INFORMATION

- Tilting log saw
  - Compact design & mobile
- Carbide (widia) saw blade 700mm
  - Support for longer pieces
    - Cardan drive
- Long-term sawing without problems
  - Return unit with spring
- Maximum capacity spar 240mm

### DESCRIPTION

Robust, all-steel tilting log saw for quick, easy and safe cutting of firewood. This tilting log saw for firewood is fully compliant with the CEN safety standards for this type of machinery. Includes zero voltage protection on the switch for improved safety in the event of voltage loss. The cover prevents you from getting near the saw blade while working, greatly reducing the risk of accidents. This tilting log saw is equipped with a saw blade in high quality carbide (widia) with diameter Ø700mm. This model is equipped with a three-point hitch and connection for PTO shaft. The machine can thus be powered by a tractor. Transmission to the saw blade with belt drive. Extremely suitable for cutting branches or tree trunks with a maximum thickness of 240mm. The tilting saw is equipped with an automatic return unit using a spring. The saw blade is effortless to operate and cuts quickly through the wood. Saw large quantities of wood in one go without any problems and ergonomically. Using the extendable support and size indication, you can cut even longer pieces to the same size. Equipped with a sturdy base with two wheels and a pull rod which makes it easy to move the machine. Easy to move, both indoors and outdoors and on uneven surfaces. Couple this tilting log saw to your tractor to be able to use it directly anywhere. Fully assembled on delivery and ready to use.

No video available for this product!

## DOWNLOADS

No download available.

## ADDITIONAL INFORMATION

<b>Weight</b>	130 kg
<b>Dimensions</b>	105 × 85 × 110 cm
<b>Motor</b>	7 HP
<b>Diameter sawblade</b>	700mm
<b>Max. cutting diameter</b>	240mm