

HELICAL PLANING AND ROUTING CUTTERHEAD 76,5MM (Z=12)



€190,08 - €208,26 (excl. VAT)

Helical planing and routing cutterhead with reversible knives in high quality carbide (HW). This cutter head is developed for finishing, planing or calibrating on moulding machines. Optionally you can use a mold and run-up ring to make curved workpieces. Thanks to the tungsten carbide blades, this cutterhead cuts effortlessly through solid boards, hard and soft woods, MDF or laminated boards.

Available with bore 30mm or 50mm. The heads can be fitted with spurs on one or both sides on demand.


SKU: N/A





VARIATIONS

lmage	SKU	Description	Shaft diameter	Price
	ST-TH74TA01-30		50 mm	€208,26 (excl. VAT)
			30 mm	€190,08 (excl. VAT)

GALERIJAFBEELDINGEN







Helical planing and routing cutterhead with reversible knives in high quality carbide (HW). This cutter head is



developed for finishing, planing or calibrating on moulding machines. Optionally you can use a mold and runup ring to make curved workpieces. Thanks to the tungsten carbide blades, this cutterhead cuts effortlessly through solid boards, hard and soft woods, MDF or laminated boards.

Available with bore 30mm or 50mm. The heads can be fitted with spurs on one or both sides on demand.

PRODUCT INFORMATION

- For spindle moulder machines
 - For finishing or calibrating
- Use a mold to make curved pieces
 - For laminated panels or MDF
 - · Hard and soft wood

DESCRIPTION

Helical planing and routing cutterhead with reversible knives in high quality carbide (HW). This cutter head is developed for finishing, planing or calibrating on moulding machines. Optionally you can use a mold and runup ring to make curved workpieces. Thanks to the tungsten carbide blades, this cutterhead cuts effortlessly through solid boards, hard and soft woods, MDF or laminated boards.

Available with bore 30mm or 50mm. The heads can be fitted with spurs on one or both sides on demand.

No video available for this product!

DOWNLOADS

No download availble.

ADDITIONAL INFORMATION

Weight 1 kg

diameter

Shaft diameter 30 mm, 50 mm



Cutting edges 12

Height of groove 76,5mm

RPM Min-Max 6000-17600