

## HOT MELT EDGE BANDER PEB250TA+









**€3 .986,70 (excl. VAT)**

Portable edge bander PEB250+ mounted in an extendable table for stationary processing of larger pieces. This edge bander with glue pot, glues PVC, ABS, melamine or wood edges to straight, round or shaped panels without any problems. The machine is suitable for processing edge bands with thicknesses between 0.4-3mm and 10-62mm height. The model PEB250+ has speed and temperature control. Table equipped with holder for rolls and automatic end trimmer.

The edge bander PEB250TA, like all other Virutex models, is fitted with a patented Teflon® coated adhesive container. This coating offers some very important advantages over other, similar machines. After use, it is very easy to clean the glue container again, which makes this edge bander much easier to maintain.

**SKU:** VIR-PEB250TA

## GALERIJAFBEELDINGEN



Portable edge bander PEB250+ mounted in an extendable table for stationary processing of larger pieces. This edge bander with glue pot, glues PVC, ABS, melamine or wood edges to straight, round or shaped panels without any problems. The machine is suitable for processing edge bands with thicknesses between 0.4-3mm and 10-62mm height. The automatic rollers and feed with guide system ensure that the edgebanding always lands correctly on your panel. The height and thickness of the edgebanding is very easy to adjust using the millimetre control. Finally, the machine also has an adjustable glue dosage so that you always use the right

quantity for your workpiece.

With the portable edge bander PEB250+ both the speed of the rollers and the temperature can be controlled. This makes the PEB250+ very suitable to work on moulded panels. The speed control allows you to always use the correct speed in function of the work. This ability offers greater working comfort on moulded panels. The table is equipped with a holder for rolls and an automatic end trimmer. The edge bander can be easily removed from the table for mobile work. In that case you must use pre-cut edge bands.

#### **Patented glue pot**

The edge bander PEB200TRC or PEB250TRC is, like all other Virutex models, fitted with a patented Teflon® coated adhesive container. This coating offers some very important advantages over other, similar machines.

After use, it is very easy to clean the glue container again, which makes this edge bander much easier to maintain. This also means that you can use other colored adhesives quickly and without any problems. No additional adjustments are required to change the glue between two projects, even if it's differently colored.

The adhesive rollers have been polymerised to prevent damage to your edge bands.

### **PRODUCT INFORMATION**

- Portable edge bander
- Automatic end trimmer
- PEB250+ with speed and temperature control & glue dosage
  - Patented Teflon® glue pot (230cm<sup>3</sup>)
  - Automatic rollers and guiding system
  - For straight, round or shaped panels
    - Thickness 0,4mm - 3mm
    - Thickness 10mm - 62mm
- Gluing roller with polymerization processing

### **DESCRIPTION**

Portable edge bander PEB250+ mounted in an extendable table for stationary processing of larger pieces. This edge bander with glue pot, glues PVC, ABS, melamine or wood edges to straight, round or shaped panels without any problems. The machine is suitable for processing edge bands with thicknesses between 0.4-3mm and 10-62mm height. The automatic rollers and feed with guide system ensure that the edgebanding always lands correctly on your panel. The height and thickness of the edgebanding is very easy to adjust using the millimetre control. Finally, the machine also has an adjustable glue dosage so that you always use the right

quantity for your workpiece. With the portable edge bander PEB250+ both the speed of the rollers and the temperature can be controlled. This makes the PEB250+ very suitable to work on moulded panels. The speed control allows you to always use the correct speed in function of the work. This ability offers greater working comfort on moulded panels. The table is equipped with a holder for rolls and an automatic end trimmer. The edge bander can be easily removed from the table for mobile work. In that case you must use pre-cut edge bands.

#### Patented glue pot

The edge bander PEB200TRC or PEB250TRC is, like all other Virutex models, fitted with a patented Teflon® coated adhesive container. This coating offers some very important advantages over other, similar machines.

After use, it is very easy to clean the glue container again, which makes this edge bander much easier to maintain. This also means that you can use other colored adhesives quickly and without any problems. No additional adjustments are required to change the glue between two projects, even if it's differently colored.

The adhesive rollers have been polymerised to prevent damage to your edge bands.

#### DOWNLOADS

No download available.

#### ADDITIONAL INFORMATION

<b>Weight</b>	30 kg
<b>Input Power</b>	830W
<b>Capacity glue container</b>	230cm <sup>3</sup>
<b>Working temperature (adjustable)</b>	120 - 200°C
<b>Working speed (adjustable)</b>	2-6m/min
<b>Min-Max. height of edge band</b>	10-62mm
<b>Min-Max. thickness of edge band</b>	0.4-3mm