

LATHE ITAMAC T-40 TURBO



€2 .851,24 (excl. VAT)

The Itamac T-40 Turbo is an example of proven technology, high-quality workmanship and ergonomic design. This wood lathe with spindle drive by a powerful 3 HP industrial servo motor has high torque, high speed (60-4300 rpm) and an overload capacity of no less than 300%.

SKU: HAR-T40

GALERIJAFBEELDINGEN



The Itamac T-40 Turbo is an example of proven technology, high-quality workmanship and ergonomic design.

This wood lathe with spindle drive by a powerful 3 HP industrial servo motor has high torque, high speed (60-4300 rpm) and an overload capacity of no less than 300%.

The head swivels 90°, for example for turning large diameter bowls. The live center is made of carbon alloy steel. The body is fitted with a durable black stoving varnish, making it more resistant to scratches, chipping and wear. All components are made of high-quality materials.

The large hand wheel of the head stock allows for smooth and easy operation and safety.

PRODUCT INFORMATION

- Powerful 3 HP industrial servo motor
 - High torque and high speed
 - 300% overload capacity
 - Head swivels up to 90°
- Live center made of carbon alloy steel
- Thanks to the stoving varnish, the machine is more resistant to scratches, chipping, and wear.
- Large handwheel offers ease of operation and safety

DESCRIPTION

The Itamac T-40 Turbo is an example of proven technology, high-quality workmanship and ergonomic design.

This wood lathe with spindle drive by a powerful 3 HP industrial servo motor has high torque, high speed (60-4300 rpm) and an overload capacity of no less than 300%. The head swivels 90°, for example for turning large diameter bowls. The live center is made of carbon alloy steel. The body is fitted with a durable black stoving varnish, making it more resistant to scratches, chipping and wear. All components are made of high-quality materials. The large hand wheel of the head stock allows for smooth and easy operation and safety.

No video available for this product!

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	80 kg
Working diameter over guideway	360 mm
Working diameter support	260 mm
Distance between centers	610 mm
Rotating head	Yes

Voltage	230 V
RPM Min-Max	60-4300
Motor	3 HP
Taper of tailstock sleeve	MT 2
Thread	M33
Length of tool rest	305 mm