MANUAL EDGEBANDER AG98R

€415,69 (excl. VAT)

Manual edgebander for edgebanding pre-glued PVC, melamine or veneer to panels. The special design with adjustable clamps on both sides of the panel ensures high precision and great stability. The machine offers the possibility of surface gluing or with an excess on both sides. Setup time: less than a minute. This edgebander can be used on flat, concave or convex workpieces.

This model of edgebander has a special double feed to use edge bands with a thickness greater than 1mm. These thicker edgebands must be fed pre-cut and manually with a maximum width of 25mm. The maximum thickness is 3mm. For edgebands of less than 1mm thickness and a maximum width of 50mm, a standard holder for rolls is included.

SKU: VIR-AG98R

GALERIJAFBEELDINGEN

Manual edgebander for edgebanding pre-glued PVC, melamine or veneer to panels. The special design with adjustable clamps on both sides of the panel ensures high precision and great stability. The machine offers the possibility of surface gluing or with an excess on both sides. Setup time: less than a minute. This edgebander can be used on flat, concave or convex workpieces. With the help of a practical cutting system, it is easy to trim edges. Maximum thickness and width of the edge bands is 1x50mm.

This model of edgebander has a special double feed to use edge bands with a thickness greater than 1mm. These thicker edgebands must be fed pre-cut and manually with a maximum width of 25mm. The maximum

thickness is 3mm. For edgebands of less than 1mm thickness and a maximum width of 50mm, a standard holder for rolls is included.

PRODUCT INFORMATION

- Manual edge bander
- Max thickness and width with holder for rolls 1x50mm
- Max dikte en breedte manual feed 3x25mm
- For pre-glued edges
- Cutting system
- Heat gun

DESCRIPTION

Manual edgebander for edgebanding pre-glued PVC, melamine or veneer to panels. The special design with adjustable clamps on both sides of the panel ensures high precision and great stability. The machine offers the possibility of surface gluing or with an excess on both sides. Setup time: less than a minute. This edgebander can be used on flat, concave or convex workpieces. With the help of a practical cutting system, it is easy to trim edges. Maximum thickness and width of the edge bands is 1x50mm. This model of edgebander has a special double feed to use edge bands with a thickness greater than 1mm. These thicker edgebands must be fed pre-cut and manually with a maximum width of 25mm. The maximum thickness is 3mm. For edgebands of less than 1mm thickness and a maximum width of 50mm, a standard holder for rolls is included.

No video available for this product!

DOWNLOADS

No download availble.

ADDITIONAL INFORMATION

Weight	2,8 kg
Max. edgeband width (thickness 1mm)	50mm

Max. edgeband width (thickness 3mm)	25mm
Temperature settings	1: 300°C, 2: 525°C
Air Flow	400l/min