

PANEL SAW ITAMAC MAESTRO X7 CNC 3200MM



€15 .750,00 (excl. VAT)

Panel saws for the professional: spacious roller table, start/stop system in sliding system, optimum ease of use. Wide tables for precision on large panels. Powerful motors, poly-belt drive. Foldaway Orca-S19 protective cover adjustable by gas spring. Digital readout of both the rip fence and saw blade tilt.



The height adjustment and tilting of the saw blade are electrically controlled, and via CNC control the ripfence is set automatically from the control panel, which is easy to operate from the top. This panel saw is available in three-phase 400V or three-phase 230V.



[View catalogue](#)

SKU: N/A

VARIATIONS

Image	SKU	Description	Voltage	Price
	IT-M3200X7CNC400	5.5 HP	3 x 400V	€15 .750,00 (excl. VAT)
	IT-M3200X7CNC230	5.5 HP	3 x 230V	€15 .750,00 (excl. VAT)

GALERIJAFBEELDINGEN



This panel saw is equipped with a spacious anodised aluminium roller table on double wear-resistant bar guide, fitted with replaceable rollers. The built-in start/stop system is located in the sliding system (roller table), so you don't have to bend down under your workpiece to switch the saw on or off, ensuring optimum ease of use and huge time savings. Thanks to the wide tables at the front and back, there is a spacious working surface that ensures more precision when machining panels.

For optimum safety and dust extraction, the overarm dust hood mechanically adjusts to the height of the workpiece. The arm can also be easily swivelled away. Moreover, the dust hood is equipped with a gas spring

for quick height adjustment.

The aluminium sliding system is fully anodised, providing strength and protection against rust. The heavy-duty dovetail suspension SE70XL, made of a single cast iron piece, absorbs vibrations, offering even more precision and stability. The well-considered design ensures optimum dust extraction.

The panel saw is powered by powerful induction motors, with the two separate motors powered by industrial poly-belts. This guarantees a reliable and powerful belt drive.

This panel saw offers not only excellent performance, but also smooth movement and reliability. **The height adjustment and tilting of the saw blade are electrically controlled, and via CNC control, the rip fence can be set automatically from the control panel, which is easy to operate from the top. This panel saw is available in three-phase 400V or three-phase 230V. It is available in three-phase 400V or three-phase 230V.**

PRODUCT INFORMATION

- Low-maintenance double sliding – 375 mm wide
- Built-in start/stop system in the sliding system for time-saving and ease of use
 - Automatic CNC-controlled rip fence
- Electrically adjustable cutting height and saw blade tilt
 - Solid tables on the back and right side
 - Precision ground cast iron work tables
- Powerful 5.5 HP and 3/4 HP TEFC induction motors
 - Heavy-duty dovetail suspension SE70XL
- Industrial high-performance belt drive with poly-belt
 - Overarm dust extractor Orca-S19
 - Digital readout of the rip fence
- Digital readout of the inclined saw blade (45°)

This panel saw is equipped with a spacious anodised aluminium roller table on double wear-resistant bar guide, fitted with replaceable rollers. The built-in start/stop system is located in the sliding system (roller table), so you don't have to bend down under your workpiece to switch the saw on or off, ensuring optimum ease of use and huge time savings. Thanks to the wide tables at the front and back, there is a spacious working surface that ensures more precision when machining panels.

For optimum safety and dust extraction, the overarm dust hood mechanically adjusts to the height of the workpiece. The arm can also be easily swivelled away. Moreover, the dust hood is equipped with a gas spring for quick height adjustment.

The aluminium sliding system is fully anodised, providing strength and protection against rust. The heavy-duty dovetail suspension SE70XL, made of a single cast iron piece, absorbs vibrations, offering even more precision and stability. The well-considered design ensures optimum dust extraction.

The panel saw is powered by powerful induction motors, with the two separate motors powered by industrial poly-belts. This guarantees a reliable and powerful belt drive.

This panel saw offers not only excellent performance, but also smooth movement and reliability. **The height adjustment and tilting of the saw blade are electrically controlled, and via CNC control, the rip fence can be set automatically from the control panel, which is easy to operate from the top. This panel saw is available in three-phase 400V or three-phase 230V.**

DESCRIPTION

This panel saw is equipped with a spacious anodised aluminium roller table on double wear-resistant bar guide, fitted with replaceable rollers. The built-in start/stop system is located in the sliding system (roller table), so you don't have to bend down under your workpiece to switch the saw on or off, ensuring optimum ease of use and huge time savings. Thanks to the wide tables at the front and back, there is a spacious working surface that ensures more precision when machining panels. For optimum safety and dust extraction, the overarm dust hood mechanically adjusts to the height of the workpiece. The arm can also be easily swivelled away. Moreover, the dust hood is equipped with a gas spring for quick height adjustment. The aluminium sliding system is fully anodised, providing strength and protection against rust. The heavy-duty dovetail suspension SE70XL, made of a single cast iron piece, absorbs vibrations, offering even more precision and stability. The well-considered design ensures optimum dust extraction. The panel saw is powered by powerful induction motors, with the two separate motors powered by industrial poly-belts. This guarantees a reliable and powerful belt drive. This panel saw offers not only excellent performance, but also smooth movement and reliability. **The height adjustment and tilting of the saw blade are electrically controlled, and via CNC control, the rip fence can be set automatically from the control panel, which is easy to operate from the top. This panel saw is available in three-phase 400V or three-phase 230V. It is available in three-phase 400V or three-phase 230V.**

No video available for this product!

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	900 kg
Voltage	3 x 230V, 3 x 400V
Motor	4 HP, 5.5 HP
Diameter sawblade	300mm, 315mm
Shaft diameter	30 mm
Cutting depth 90 °	102 mm
Cutting depth 45°	76 mm
Saw blade speed	4000
Scorer diameter	120 mm
Scorer arbor	20 mm
Scorer speed	8000 RPM
Sliding system	3200 mm x 375 mm
Max. cutting length	3200 mm
Dust collection port	100 mm
Tilt	45°
Working height	875mm
Max. width left saw blade	3200 mm
Max. width right saw blade	1300 mm
Cast iron work table	535 mm x 800 mm
Right table	800 mm x 820 mm
Rear table	535 mm x 435 mm
Min. needed space	3350 mm x 6800 mm

YOU MAY ALSO LIKE...



**READY
toWORK**

READYtoWORK
package Panel saw
ITAMAC Maestro X7
CNC 3200mm