

PIHER - PULLEY PULLER WITH TWO FIXED LEGS



€86,37 - €286,78 (excl. VAT)

Ideal solution for the professional removal of ball bearings. These models feature fully reversible legs. Under extreme pressure, the body can be elastically deformed to prevent breakage. Electrolytic nickel coated. Available in different sizes.

SKU: N/A

VARIATIONS

| Image | SKU | Description | Maximum opening | Price |
|---|-----------|-------------------------------------|-----------------|---------------------|
|  | PIH-72209 | Arm length: 50mm Pull force: 1 Tn | 60mm | €86,37 (excl. VAT) |
|  | PIH-72219 | Arm length: 80mm Pull force: 2 Tn | 80mm | €111,92 (excl. VAT) |
|  | PIH-72229 | Arm length: 135mm Pull force: 3 Tn | 115mm | €134,81 (excl. VAT) |
|  | PIH-72239 | Arm length: 220mm Pull force: 10 Tn | 145mm | €245,92 (excl. VAT) |

| Image | SKU | Description | Maximum opening | Price |
|---|-----------|-------------------------------------|-----------------|---------------------|
|  | PIH-72238 | Arm length: 160mm Pull force: 10 Tn | 155mm | €229,42 (excl. VAT) |
|  | PIH-72249 | Arm length: 220mm Pull force: 15 Tn | 195mm | €286,78 (excl. VAT) |

Ideal solution for the professional removal of ball bearings. These models feature fully reversible legs. Under extreme pressure, the body can be elastically deformed to prevent breakage. Electrolytic nickel coated.
Available in different sizes.

PRODUCT INFORMATION

- Ideal solution for the professional removal of ball bearings
 - Fully reversible legs
- Under extreme pressure, the body can be elastically deformed to prevent breakage
 - Electrolytic nickel coated

DESCRIPTION

Ideal solution for the professional removal of ball bearings. These models feature fully reversible legs. Under extreme pressure, the body can be elastically deformed to prevent breakage. Electrolytic nickel coated.
Available in different sizes.

No video available for this product!

DOWNLOADS

No download availble.

ADDITIONAL INFORMATION

| | |
|-----------------|--|
| Weight | N/A |
| Maximum opening | 60mm, 80mm, 115mm, 145mm, 155mm, 195mm |
| arm length | 50mm, 80mm, 135mm, 160mm, 220mm |
| Maximum force | 1 Tn, 2 Tn, 3 Tn, 10 Tn, 15 Tn |