

PIHER - VISE WITH SQUARE JAWS



€156,56 - €359,33 (excl. VAT)

These heavy duty square-jawed vises are made from C-40 forged steel and are therefore super strong. They have adjustable square jaws that can be replaced, feature an anvil base and come standard with magnetic aluminum pressure plates. You can easily mount the vises through the provided holes. You can also mount them in an optional rotatable base. Available in three sizes. A real must for the serious workshop!

SKU: N/A



VARIATIONS

| Image | SKU | Description | jaw width | Price |
|-------|-----------|---|-----------|---------------------|
| rnas | PIH-55100 | Clamp thickness: 10.5 cm Clamp height: 6.5cm | 10cm | €156,56 (excl. VAT) |
| Falas | PIH-55125 | Clamp thickness: 13cm Clamp height: 8cm | 12,5cm | €192,45 (excl. VAT) |
| ran | PIH-55150 | Clamp thickness: 16.5 cm Clamp height: 10cm | 15cm | €359,33 (excl. VAT) |

GALERIJAFBEELDINGEN







These heavy duty square-jawed vises are made from C-40 forged steel and are therefore super strong. They have adjustable square jaws that can be replaced, feature an anvil base and come standard with magnetic aluminum pressure plates. You can easily mount the vises through the provided holes. You can also mount them in an optional rotatable base. Available in three sizes. A real must for the serious workshop!

PRODUCT INFORMATION

- Made from C-40 forged steel with a hardness of 45-51 HRC
 - Interchangeable jaws
 - Anvil base
 - Includes magnetic aluminum pressure plates

DESCRIPTION

These heavy duty square-jawed vises are made from C-40 forged steel and are therefore super strong. They have adjustable square jaws that can be replaced, feature an anvil base and come standard with magnetic aluminum pressure plates. You can easily mount the vises through the provided holes. You can also mount them in an optional rotatable base. Available in three sizes. A real must for the serious workshop!

No video available for this product!



DOWNLOADS

No download availble.

ADDITIONAL INFORMATION

Weight N/A

jaw width 10cm, 12,5cm, 15cm

Maximum clamping thickness 10,5cm, 13cm, 16,5cm