

SPINDLE MOULDER COMFORT-LINE TT110CA



~~€1.900,00~~ **€1.611,57 (excl. VAT)**

Compact but powerful spindle moulder from our comfort line, suitable for use in any small workshop or at home. The machine can be used at four speeds and is driven by a 230V or 400V motor that delivers 3HP.

This allows the machine to process a wide range of applications.

Now delivered with free options:

- **Additional spindle shaft for routers**
- **Aluminium safety guides**
- **Miter guide**
- **Table extension left and right**

SKU: OSP110CA

VARIATIONS

Image	SKU	Description	Voltage	Price
	OSP110CAS	3 HP	230 V	€1.900,00 <u>€1.611,57</u> (excl. VAT)
	OSP110CAT	3 HP	3 x 400V	€1.900,00 <u>€1.611,57</u> (excl. VAT)

GALERIJAFBEELDINGEN





Compact but powerful spindle moulder from our comfort line. Suitable for use in every small workshop or at home. The machine can be used at four speeds and is driven by a 230V or 400V motor that delivers 3HP. This allows the machine to handle a wide range of applications. It is suitable for standard milling work, tenoning, rebating and more. Because of the low speed of 1400rpm, this spindle moulder is also suitable for sanding work. The speeds are clearly indicated in the side door with a large viewing window.

With an optional adaptor and collet, router bits can also be used below the table. Collets of both 8-10 and 12 mm are available for this purpose.

The stable cast iron worktable is provided with a T-slot groove and optionally a convenient mitre guide. These T-slots offer many other and safe possibilities such as the use of tenoning jigs and numerous safety pushers (see BOW range). Furthermore, the work table has a stable table extension on the left and right. The safety hood has optional aluminium safety guides, which manually reduce the cutter opening and ensure better guidance, and unique spring-loaded pressure wheels to apply better pressure to the material.

The height adjustment is done with very robust metal handwheels for smooth running and on this shaft there is a clear analogue measurement indicator for precision control.

The safety coil switch is equipped with an extra-large emergency stop.

Optionally available.

Short routing spindle with collet for routers

Alu safety guides

Miter guide

Table extension left and right
Wheelbase

PRODUCT INFORMATION

- Spindle moulder 30mm
- 230 V or 400 V (3 HP) motor
- Protective cover with safety guides
 - Analogue height indication
 - Robust hand wheels
 - Easy to operate
 - T-slots in the work table
 - Miter guide
 - Four speeds
 - Tenoning
 - Profiling
 - Sanding
- Compact and sturdy design

DESCRIPTION

Compact but powerful spindle moulder from our comfort line. Suitable for use in every small workshop or at home. The machine can be used at four speeds and is driven by a 230V or 400V motor that delivers 3HP. This allows the machine to handle a wide range of applications. It is suitable for standard milling work, tenoning, rebating and more. Because of the low speed of 1400rpm, this spindle moulder is also suitable for sanding work. The speeds are clearly indicated in the side door with a large viewing window. With an optional adaptor and collet, router bits can also be used below the table. Collets of both 8-10 and 12 mm are available for this purpose. The stable cast iron worktable is provided with a T-slot groove and optionally a convenient mitre guide. These T-slots offer many other and safe possibilities such as the use of tenoning jigs and numerous safety pushers (see BOW range). Furthermore, the work table has a stable table extension on the left and right. The safety hood has optional aluminium safety guides, which manually reduce the cutter opening and ensure better guidance, and unique spring-loaded pressure wheels to apply better pressure to the material. The height adjustment is done with very robust metal handwheels for smooth running and on this shaft there is a clear analogue measurement indicator for precision control. The safety coil switch is equipped with an extra-large emergency stop. **Optionally available.** Short routing spindle with collet for routers Alu safety guides Miter guide Table extension left and right Wheelbase

No video available for this product!

DOWNLOADS

No download available.

ADDITIONAL INFORMATION

Weight	110 kg
Motor	3 HP
Voltage	230 V, 3 x 400V
Shaft diameter	30 mm
No-load speed	1400 rpm, 4000 rpm, 6000 rpm, 9000 rpm
Table opening	160 mm
Height of groove	110 mm
Worktable	620 x 510 mm