

TEMPLATE FOR ELLIPSES AND CIRCLES PE60 FOR ROUTERS



€323,09 (excl. VAT)

Guide rail or jig for circles and ovals with maximum diameter and main axis 3200mm. This compass is ideal for making mirrors, windows, doors, or any other creation with a circular or elliptical shape. To mill out an elliptical shape, use both swivel supports and elongated guides. By using just one of the two swivel supports you can mill perfect circles. Place the support exactly in the centre of the mould to make circles.

The guide rail is equipped with two powerful suction cups to attach to your panels without damage. If it is not possible to use the suction cups (e.g. on porous materials), the mould is provided with holes to screw them on. Standard delivery with two rods (Ø8mm) to attach the router to the guide.

SKU: VIR-PE60



GALERIJAFBEELDINGEN





Guide rail or jig for circles and ovals with maximum diameter and main axis 3200mm. This compass is ideal for making mirrors, windows, doors, or any other creation with a circular or elliptical shape. To mill out an elliptical shape, use both swivel supports and elongated guides. By using just one of the two swivel supports you can mill perfect circles. Place the support exactly in the centre of the mould to make circles.

The guide rail is equipped with two powerful suction cups to attach to your panels without damage. If it is not possible to use the suction cups (e.g. on porous materials), the mould is provided with holes to screw them on.

Standard delivery with two rods (Ø8mm) to attach the router to the guide.

PRODUCT INFORMATION

- Jig for routers
- Circles or ovals
- Fastening with suction cups (without damage)

DESCRIPTION

Guide rail or jig for circles and ovals with maximum diameter and main axis 3200mm. This compass is ideal for making mirrors, windows, doors, or any other creation with a circular or elliptical shape. To mill out an elliptical



shape, use both swivel supports and elongated guides. By using just one of the two swivel supports you can mill perfect circles. Place the support exactly in the centre of the mould to make circles. The guide rail is equipped with two powerful suction cups to attach to your panels without damage. If it is not possible to use the suction cups (e.g. on porous materials), the mould is provided with holes to screw them on. Standard delivery with two rods (Ø8mm) to attach the router to the guide.

DOWNLOADS

No download availble.

ADDITIONAL INFORMATION

Weight 3 kg

Minimum small axis (ellips) 600mm

Maximum large axis (ellips) 3200mm

Minimum diameter (circle) 600mm

Maximum diameter (circle) 3200mm