

## WOODTURNING LATHE ITAMAC WL-508DC



**€979,34 (excl. VAT)**

The Itamac WL-508DC is a very stable, with **vario-inverter** speed control, left and right turning wood lathe with a turning diameter of 320 mm and 508 mm between the points. The speed can be regulated steplessly in 3 ranges between 250 and 3850 rpm. (250-750 / 550-1650 / 1300-3850 rpm). The vario-inverter can maintain a constant torque at any speed, so even at low rpm it still delivers very powerful torque. The motor is a low-noise DC motor of 1000 Watts.

**SKU:** IT-LAWL508DC

## GALERIJAFBEELDINGEN



The Itamac WL-508DC is a very stable, with **vario-inverter** speed control, left and right turning wood lathe with a turning diameter of 320 mm and 508 mm between the points. The speed can be regulated steplessly in 3 ranges between 250 and 3850 rpm. (250-750 / 550-1650 / 1300-3850 rpm). The vario-inverter can maintain a constant torque at any speed, so even at low rpm it still delivers very powerful torque. The motor is a low-noise DC motor of 1000 Watts. With this compact wood lathe, attention has been paid to turning as quietly and vibration-free as possible. Very user-friendly operation with a rotary knob for stepless speed control and digital display of speed and direction of rotation.

The three-stage wide polybelt pulleys can be changed very quickly and easily, and thus the speed range can be adjusted easily and quickly. This lathe has a wide and solid bed and therefore also maximum stability during

turning! The 200 mm wide support slides easily up and down the bed and has a nice 45° bevelled edge.

### PRODUCT INFORMATION

- DC motor 1000 Watts
  - Poly belt drive
  - Vario inverter
- 3 speed ranges (250-750/550-1650/1300-3850 rpm)
  - Very powerful torque
  - Left and right rotating
- Electronically adjustable speed
  - Digital speed display
- Smooth changeover forward/backward
  - Stable and quiet
  - Quick belt change
- Spindle with thread M33 x 3.5 mm
- Movable head with wide trapezoidal thread

### DESCRIPTION

The Itamac WL-508DC is a very stable, with **vario-inverter** speed control, left and right turning wood lathe with a turning diameter of 320 mm and 508 mm between the points. The speed can be regulated steplessly in 3 ranges between 250 and 3850 rpm. (250-750 / 550-1650 / 1300-3850 rpm). The vario-inverter can maintain a constant torque at any speed, so even at low rpm it still delivers very powerful torque. The motor is a low-noise

DC motor of 1000 Watts. With this compact wood lathe, attention has been paid to turning as quietly and vibration-free as possible. Very user-friendly operation with a rotary knob for stepless speed control and digital display of speed and direction of rotation. The three-stage wide polybelt pulleys can be changed very quickly and easily, and thus the speed range can be adjusted easily and quickly. This lathe has a wide and solid bed and therefore also maximum stability during turning! The 200 mm wide support slides easily up and down the bed and has a nice 45° bevelled edge.

No video available for this product!

### DOWNLOADS

No download available.

## ADDITIONAL INFORMATION

<b>Weight</b>	53 kg
<b>Dimensions</b>	1020 × 305 × 470 cm
<b>Distance between centers</b>	508 mm
<b>Voltage</b>	230 V
<b>Thread</b>	M33
<b>Taper of tailstock sleeve</b>	MT 2
<b>Working diameter over guideway</b>	320 mm
<b>Travel of tailstock sleeve</b>	63 mm
<b>RPM Min-Max</b>	250 - 3850
<b>Rotating head</b>	No